

Polyvalent mulcher for the elimination of remains of pruning, in citrus fruits, fruit trees, olive trees and clear of matter in foot.

Rear hydraulic gate with sieve, replaceable breakers and roller of control for the soil. It allows to be employed at both directions, attacking big volumes, at the same hooking

It protects the tractor of pricks and breakdowns not having to tread on the material to mulch.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 550 mm.
- ► Gearbox SERRAT.
- ▶ 3/4 XPC side belt transmission.
- ► Forged agricultural hammers SERRAT.
- ► Hammers guaranteed against breakage.
- ► GIROSTOP System.
- ▶ Supports of bearing rotor in steel.
- ► High speed and high strength bearings.
- ► Front protection curtain.
- ▶ Obturations antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable roller Ø 210 mm.

- ▶ PTO 540 rpm.
- ▶ Rear hydraulic hood with sieve.
- ► Rear roller cleaner.
- ▶ 7 lines of counter hammers.
- ► Front skid shoes.
- ▶ Model built under EC Normative.
- ► Safety indicators visible to personnel.



System antiwire in rotor



Rear hood with sieve



	MODEL			R	KG	N° BELTS							
		mm	KW-HP			ТҮРЕ	A mm	A in	B mm	B in	C mm	C in	
ı	T-1400	1400	48 - 65 96 - 130	12	853	3 XPC	1621	64"	1345	53"	1150	45"	540
ı	T-1500	1500	51 - 70 96 - 130	12	880	3 XPC	1721	68"	1345	53"	1150	45"	540
ı	T-1600	1600	55 - 75 96 - 130	12	913	3 XPC	1821	72"	1345	53"	1150	45"	540
	T-1800	1800	59 - 80 96 - 130	16	986	3 XPC	2021	80"	1345	53"	1150	45"	540
ı	T-2000	2000	63 - 85 96 - 130	16	1079	4 XPC	2221	87"	1345	53"	1150	45"	540
	T-2300	2300	66 - 90 96 - 130	20	1175	4 XPC	2521	99"	1345	53"	1150	45"	540

OPTIONS



► Front skid shoes



Freewheel on transmission



► Freewheel on sleeve



► Height adjustable rear roller



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es





The data presented in this catalog are provided for information purposes only and are not binding.