



Mulcher with reversible hydraulic feeder, ideal for chestnut-trees, olive trees, almond-trees, citrus fruits, etc.

Mulcher with rear sieve, to adjust the granulometry of the product.

It has a rotor POLSER, with GIROSTOP System, capable of mulching remains of prunings up to 10-12 cm.

It is proposed appears with two hookings: front lift and rear lift.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 550 mm.
- ▶ Gearbox SERRAT.
- ▶ 4 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ Hammers guaranteed against breakage.
- ▶ Feeder with system BRALAKC.
- ▶ High torque hydraulic motor reversible.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ PTO 540 rpm.
- ▶ Rear height-adjustable roller Ø 210 mm.
- ▶ Triple feed chain.
- ▶ GIROSTOP System.
- ▶ Double bearing on rear roller.
- ▶ Reversible toothed rear screen.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Feeder Bralack



Screen replaceable rear gear



MODEL	mm	KW-HP	Tractor icon	Swan icon	KG icon	Nº BELTS TYPE	Diagram					
							A mm	A in	B mm	B in	C mm	C in
T-1500	1500	59 - 80 103 - 140	12	1262	4 XPC	1791	70"	1612	63"	1263	50"	540 1000
T-1800	1800	63 - 85 103 - 140	16	1416	4 XPC	2091	82"	1612	63"	1263	50"	540 1000
T-2000	2000	66 - 90 103 - 140	16	1490	4 XPC	2291	90"	1612	63"	1263	50"	540 1000
T-2300	2300	81 - 110 103 - 140	20	1646	4 XPC	2591	102"	1612	63"	1263	50"	540 1000

OPTIONS



▶ Freewheel on sleeve



▶ Preparation for front lift (gearbox)



▶ Rear wheels



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.