SECTOL REVERSIBLE SIDE SHIFT SEKURLAST

EVOLUTION





Mulcher of hammers, for the elimination of remains of pruning up to 80 mm and maintenance of vegetable mantle. Ideal for the regeneration of meadows and grassland.

Rotor POLSER of 450-500 mm of diameter.

Excellent results in industrial gardening and maintenance of borders.

Its reversible and movable configuration allows to drive the machine well in the rear power lift as in the front in reversible tractors avoiding to tread on the material to mulch.

CHARACTERISTICS

- ► Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450/500 mm.
- ► Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ► Forged agricultural hammers SERRAT.
- ► GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ► High speed and high strength bearings.
- ► Front protection curtain.

- ► System antiwire in rotor.
- ▶ Double bearing on rear roller.
- ► Rear height-adjustable roller Ø 180 mm (210 mm from T-2300).
- ▶ PTO 540 rpm (1,000 rpm from T-2500).
- ▶ 1,000 rpm for front PTO.
- ► Rear roller cleaner.
- ▶ Steel counter hammers.
- ▶ Model built under EC Normative.
- ► Safety indicators visible to personnel.



System antiwire in rotor



MODEL					KG	Nº BELTS TYPE							
_		mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
450 POLSER	T-1600	1600	44 - 60 88 - 120	12	810	3 XPC	1790	70"	1450	57"	950	37"	540
	T-1800	1800	48 - 65 88 - 120	16	861	3 XPC	1990	78"	1450	57"	950	37"	540
	T-2000	2000	51 - 70 88 - 120	16	916	3 XPC	2190	86"	1450	57"	950	37"	540
	T-2300	2300	59 - 80 88 - 120	20	1023	3 XPC	2490	98"	1450	57"	950	37"	540
500 POLSER	T-2500	2500	66 - 90 88 - 120	20	1152	3 XPC	2690	106"	1450	57"	980	39"	1000
	T-2800	2800	74 - 100 88 - 120	24	1235	3 XPC	2990	118"	1450	57"	980	39"	1000

OPTIONS

► Rear wheels



► Rear tine retaines



► Front chains

▶ Freewheel



► Front adjustable skid shoes

▶ Green



► Front wheels

► Gearbox 1.000 RPM for front PTO



► Reinforced roller



► Super hydraulic side shift



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es





The data presented in this catalog are provided fo information purposes only and are not binding.