



Mulcher combined of great power for tractors up to 270 HP. Perfect for punctured of maize, sorghum, sunflower, cotton and meadow in big extensions.

It incorporates hydraulic rear hood with turn arble nozzles, to extend the matter uniformly.


Double geardrives of traction, which guarantees a perfect transmission of power between the tractor and the rotor. Rotor POLSER of 725 mm of diameter equipped with different elements of cut: blades or hammers.

CHARACTERISTICS


- ▶ Steel-plate chassis, thickness 12 mm.
- ▶ Rotor POLSER of Ø 725 mm.
- ▶ Gearbox with freewheel up to 270 HP.
- ▶ 2 x 4 XPC side belt transmission.
- ▶ Stamped hammers or Y blades.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ System antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear roller Ø 280 mm.
- ▶ PTO 1,000 rpm.
- ▶ Rear hydraulic hood.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Rear hydraulic hood










System antiwire in rotor



Rear roller Ø 280 mm



MODEL	 mm	 KW-HP			 KG	Nº BELTS TYPE							
							A mm	A in	B mm	B in	C mm	C in	
T-2800	2800	89 - 120 147 - 200	28	84	2316	2 x 4 XPC	3153	124"	2290	90"	1295	51"	1000
T-3200	3200	104 - 140 147 - 200	32	96	2510	2 x 4 XPC	3553	140"	2290	90"	1295	51"	1000
T-3800	3800	119 - 160 147 - 200	32	96	2845	2 x 4 XPC	4153	163"	2290	90"	1295	51"	1000
T-4600	4600	134 - 180 161 - 220	40	120	3150	2 x 4 XPC	4980	196"	2290	90"	1295	51"	1000
T-6500	6500	149 - 200 198 - 270	56	168	3430	2 x 4 XPC	6880	271"	2290	90"	1295	51"	1000


OPTIONS



▶ Adjustable nozzle




▶ Hammers



▶ Blades in Y-form



▶ Front chains



▶ Front adjustable skid shoes



▶ Adjustable wheels

