



Heavy-duty high body mulcher conceived for very large farms and agricultural contractors. Robust machine designed for very intensive mulching, intended for mulching grass in park maintenance, straw, maize stalks, and on fallow land. Composition for big tractors reaching a working width of 10 meters with a front machine of 2,80 m of working width avoiding to tread on the material to mulch. The innovative and practical device for opening and closing the rotors is equipped with special hitches and safety valves for transport. The 600 mm diameter mulching rotor delivers maximum throughput. A heavy steel beam forms a fixed leveling point, relative to which the two rotor structure can be lifted and lowered, the two rotor can work independently of each other. It gives also better users visibility across the whole working width. The inside gearboxes transmission allows us to approach the lateral edges as close as possible to the feet of the trees and towards the field edge.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 8 mm.
- ▶ Rotor POLSER of Ø 600 mm.
- ▶ Gearbox SERRAT.
- ▶ Frontal machine 4 XPC belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ System antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable rollers.
- ▶ PTO 1,000 rpm.
- ▶ Hydraulic folding exclusive design by SERRAT.
- ▶ HIDRAHELP.
- ▶ Rear roller Ø 280 mm.
- ▶ Freewheel.
- ▶ Direct cardan rear machine.
- ▶ Composition of two machines.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



System antiwire in rotor



Hidrahelp



Hydraulic folding exclusive design by SERRAT




MODEL	mm	KW-HP	PTO	KG	Nº BELTS TYPE	Diagram						
						A mm	A in	B mm	B in	C mm	C in	
T-8400	8400	224 - 300 336 - 450	28 x 2	4560	4 XPC	8450	333"	1300	51"	1346	53"	1000
T-9500	9500	224 - 300 336 - 450	32 x 2	5080	4 XPC	9642	380"	1300	51"	1346	53"	1000
F.R.S. T-3000	3000	224 - 300 336 - 450	28	1600	4 XPC	3237	127"	1470	58"	1242	49"	1000

F.R.S.: Frontal Reversible Shide Shift.



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.