

serrat

EVOLUTION FRONTAL

450 POLSER  GIROSTOP  SEKURLAST



Mulcher designed for tractors between 60 HP to 120 HP for the maintenance of vegetable mantle and for the elimination of remains of pruning up to 80 mm.

Special configuration for frontal works.







CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ Two lines of steel counter hammers.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Rear height-adjustable roller Ø 180/210 mm (from T-2000).
- ▶ Double bearing on rear roller.
- ▶ Rear gum over the roller.
- ▶ PTO 1,000 rpm.
- ▶ Hydraulic side shift.
- ▶ Hydraulic front hood.
- ▶ Long skid shoes.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Obturations antiwire in rotor




MODEL	 mm	 KW-HP		 KG	Nº BELTS TYPE							
						A mm	A in	B mm	B in	C mm	C in	
T-1600	1600	45 - 60 90 - 120	12	720	3 XPC	1825	72"	1035	41"	995	39"	1.000
T-1800	1800	45 - 60 90 - 120	16	785	3 XPC	2025	80"	1035	41"	995	39"	1.000
T-2000	2000	45 - 60 90 - 120	16	875	3 XPC	2225	88"	1055	42"	995	39"	1.000
T-2300	2300	45 - 60 90 - 120	20	1050	3 XPC	2525	99"	1385	55"	1060	42"	1.000

OPTIONS

- ▶ Freewheel

serrat

Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.