

serrat



Mulcher with double hydraulic feeder, adapted to cut up residues up to 60-80 mm of diameter in olive trees, citrus fruits, almond trees, walnuts, etc; with interchangeable counter-knives to set the grain size, for tractors between 60 and 120 HP.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ POLSER rotor of Ø 450 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ Feeder with system BRALAKC.
- ▶ High torque hydraulic motor reversible.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ PTO 1,000 rpm.
- ▶ Rear height-adjustable roller Ø 180 mm.
- ▶ Triple feed chain.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Double bearing on rear roller.
- ▶ Reversible toothed rear screen.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Feeder BRALAKC



Reversible toothed rear screen



MODEL	mm	KW-HP	kg	Nº BELTS TYPE	Diagram							
					A mm	A in	B mm	B in	C mm	C in		
T-1600	1600	45 - 60 88 - 120	12	1059	3 XPC	1815	71"	1245	49"	1215	48"	540
T-1800	1800	60 - 80 88 - 120	16	1147	3 XPC	2015	79"	1245	49"	1215	48"	540
T-2000	2000	75 - 100 88 - 120	16	1222	3 XPC	2215	87"	1245	49"	1215	48"	540

OPTIONS


- ▶ Reversible
- ▶ Freewheel



▶ Fixed rear wheel

serrat

Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.