



Soil preparation machine up to a depth of 600 mm, for tractors between 400 - 500 HP. Transforms forest land, with stumps and rocks, in land for cultivation avoiding accidents in later processes.

CHARACTERISTICS

- Steel-plate chassis, thickness 12 mm.
- Rotor FIXE TOP of Ø 700 mm.
- Gearbox SERRAT for 500 HP with gears.
- Speed change with gears (Optional).
- Supports of bearing rotor in steel.
- Oscillating bearings of double row of rollers.
- PTO 1,000 rpm.
- Rear hydraulic hood.

- Front hydraulic hood anti projections.
- Chassis internal reinforcements, thickness 10 mm.
- Interchangeable anvil.
- System antiwire in rotor.
- Hydraulic levelling roller.
- Model built under EC Normative.
- Safety indicators visible to personnel.



1. Rear hydraulic hood
2. Hydraulic levelling roller

FIXE TOP System




*For working in depth it is recommended that the tractor has a Creeper or Vario.

MODEL	mm	KW-HP	GEARS	A		B		C		in		
				mm	in	mm	in	mm	in			
T-2500	2500	298 - 400 372 - 500	56	5500	2	2890	114"	2400	94"	1610	63"	1000
T-3000	3000	298 - 400 372 - 500	68	5800	2	3390	134"	2400	94"	1610	63"	1000



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.